

## RISEN GROUTING PUMP

### Specifications

Type:	Single piston double acting with balls in valve plate
Clutch:	Dog clutch
Pressure :	20 kg/sq cm
Stroke:	85mm
Speed:	180prm
Suction Port:	51mm(2" BSP)
Delivery Port:	42mm
Liner Bore Dia.	75mm
Transmission:	Pulley & Vee Belt
Mounting:	Skid Mounted
Flow :	130 l/min
Engine :	10 hp diesel engine
Weight :	70 kg (Bare pump) 155kg (with skid & belt cover) 260kg (Complete with ChangChai SQD192 engine)
Dimensions :	(With skid mounting) 1540mm Lx 580mm W x 940mm H

Specifications are subject to change without prior notice

### Advantages:

Compact & light weight :	The pump is so compact that it even go into the boot of a car. Body of pump is made of aluminum casting: about 2 1/2 times lighter than iron casting used by other manufacturer.
Powerful & Durable:	With a discharged pressure of 20 kg/cm <sup>2</sup> . This pump is ideal for almost all soil drilling operations.
Economical & Easy Maintenance:	Simple design makes maintenance easy and economical Easy availability of parts at reasonable prices



The information contained in this document is believed to correct but RISEN accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. Please consult the respective machine manual for all matters related to operations and maintenance.