

RPT30砂浆喷涂机



a compact and highly
efficient pump for
engineered materials

瑞申RPT30砂浆喷涂机

RPT30 Mortar Pump

应用领域
APPLICATIONS

瑞申RPT30砂浆喷涂机用于已经搅拌好的砂浆泵送、喷涂，砂浆应当具有泵送性，如水泥砂浆、石灰砂浆、石膏砂浆、保温砂浆、各种自流平砂浆及耐火材料喷涂料等。

The Risen RPT30 mortar pump is suitable for pumping and spraying the wet ready-mixed mortar which is pumpable, such as Cement mortars, Lime plasters, Gypsum plasters, Masonry mortars, Insulating plasters, Self-leveling floor screeds, etc.

技术参数
TECHNICAL DATA

技术参数Technology Description	
额定排量Rated Output	30 L/min
额定工作压力Rated Working Pressure	3 MPa
机器总功率Total Power	7.5kW
主电机Main Electric Motor	3Phase, 380volt, 5.5 kW
螺杆转速Rev. of Rotor	380 RPM
空压机排量Rated Air Output	250L/min
最大输送距离Max. Conveying Dist.	50m
料斗容积Hopper Capacity	26L
上料高度Loading Height	800mm
输送管内径Conveying Hose ID.	25/32mm
气管内径Air Hose ID.	13mm
外形尺寸(长×宽×高) Overall Dimension	1460(1220) × 600 × 1100mm*
重量Weight	190 kg

*括号内为卸掉螺杆泵尺寸

T0
RISEN
先进技术 真诚服务
郑州瑞申机器制造有限公司
Risen Machinery Co., Ltd.

地址：郑州市桐柏路43号科技大厦7层

add: 7th floor, S&T Building, No. 43

Tongbai Road, Zhengzhou, China

电话(Tel): +86 371 67770011, 67770022

传真(Fax): +86 371 67770031

 网址(Web): <http://www.risencrete.com>

 E-mail: sales@risencrete.sina.net
sales@risencrete.com