



RM 系列双层搅拌机

瑞申 RM 系列双层搅拌机主要用于搅拌水泥浆类介质。与注浆泵一起配套用于隧道开凿与维护、矿井工程、修建水坝、大型桥梁和高层建筑的基础处理工程以及各类地下工程等的压力灌浆。

RM280/520 double-layer Mixer mainly mix cement grout and similar slurry, Combine with grouting pump, it can grout with pressure in mining, tunnel, culvert, subway, hydropower engineering, underground excavation engineering etc.



RM 系列双层搅拌机工作参数(RM double-layer Mixer Technology Description)

型号 Item	混合桶容积 Mixing tank capacity	储料桶容积 Agitating tank capacity	混合转速 Mixing speed	搅拌转速 Agitating speed	主电机 Mixer Unit	辅电机 Agitating motor	外型尺寸 Dimensions	重量 Weight
RM300-580	300 L	580 L	50 r/min	33 r/min	4 kW	1.5 kW	1585×995×1500 mm	400 kg
RM300-750	300 L	750 L	550 r/min	33 r/min	4 kW	1.5 kW	1698×1118×1600 mm	500 kg

RM300-580 主要用于搅拌砂浆等适应慢速搅拌的材料；RM300-750 主要用于搅拌灰浆等适应快速搅拌的材料。
RM300-580 Cement mortar or other materials suitable for being mixed slowly, RM300-750 Grout or other materials suitable for being mixed quickly.